

# MD 10 washer disinfector



### Chamber

- 10 DIN basket capacity with the possibility of extending to 12 DIN
- usable chamber dimensions LxDxH: 550 x 620 x 685 mm
- washing chamber made of AISI 316L stainless steel
- 2 washing arms permanently installed in the chamber, one at the top and one at the bottom
- individual trolleys have additional washing arms ensuring the highest washing standard
- washing at temperatures up to 95°C
  thermal disinfection
- · LED lighting system

# Control system

- multilingual control panel with a TFT color touch screen (on both sides)
- programs: 20 default and 20 programmable
- control panel protected by a multilevel password system
- built-in printer (option)
- USB port for archiving washing cycle loas
- Ethernet port for connection to a LAN network (optional)



Instrument trolley



customizable trolley setup



OR shoe trolley



automatic trolley recognition

## Main features

- overall dimensions LxDxH: 780 x 800 x 1950 mm
- housing made of AISI 304 stainless steel
- 2 full glass vertically sliding doors
- interlocking door system, which ensures complete dirty and clean side separation
- high pressure hot air drying system with HEPA filters (99.999% efficiency)
- drying system with an airflow rate of 220 m³/h
- highly efficient Ecoslim steam condenser (option)

# Detergents

- detergent cabinet, with a removable tray, that can store up to 3 x 5l containers and 1 x 1l container
- detergent peristaltic pump with a level sensor
- neutralizer peristaltic pump with a level sensor
- possibility to install 2 additional peristaltic pumps with level sensors

## **Utilities**

- cold, hot and demineralized water connections
- floor drain connection
- drain pump (option)
- electrical connection:
  3 / N / PE 400 V 50 Hz 13 kW max

# SMS sp. z o.o.

8 Adamowicza Street 05-530 Góra Kalwaria, Poland tel. +48 22 843 27 61 fax +48 22 843 28 81 e-mail: market@sms.com.pl www.sms.com.pl