

# MD 15 washer disinfector



### Chamber

- 15 DIN basket capacity with the possibility of extending to 18 DIN
- usable chamber dimensions LxDxH: 626 x 812 x 685 mm
- washing chamber made of AISI 316L stainless steel
- 2 washing arms permanently installed in the chamber, one at the top and one at the bottom
- individual trolleys have additional washing arms ensuring the highest washing standard
- washing at temperatures up to 95°C
  thermal disinfection
- · LED lighting system

# Control system

- multilingual control panel with a TFT color touch screen (on both sides)
- programs: 20 default and 20 programmable
- control panel protected by a multilevel password system
- built-in printer (option)
- USB port for archiving washing cycle loas
- Ethernet port for connection to a LAN network (option)



Instrument trolley



■anesthesia set trolley



Itransport trolley



automatic trolley recognition

### Main features

- overall dimensions LxDxH: 900 x 1000 x 1942 mm
- housing made of AISI 304 stainless steel
- 2 full glass vertically sliding doors
- interlocking door system, which ensures complete dirty and clean side separation
- high pressure hot air drying system with HEPA filters (99.999% efficiency)
- drying system with an airflow rate of 440 m<sup>3</sup>/h
- highly efficient Ecoslim steam condenser (option)
- two independent washing pumps

# Detergents

- detergent cabinet, with a removable tray, that can store up to 4 x 5l containers and 1 x 1l container
- detergent peristaltic pump with a level sensor
- neutralizer peristaltic pump with a level sensor
- possibility to install 3 additional peristaltic pumps with level sensors

## **Utilities**

- cold, hot and demineralized water connections
- floor drain connection
- drain pump (option)
- electrical connection:
  3 / N / PE 400 V 50 Hz 20 kW max

# SMS sp. z o.o.

8 Adamowicza Street 05-530 Góra Kalwaria, Poland tel. +48 22 843 27 61

fax +48 22 843 28 81

e-mail: market@sms.com.pl www.sms.com.pl